


EQQ

Product Datasheet 9.18



Stainless Steel Square Edge Trim



Product Description

Genesis EQQ is a square edge Stainless Steel profile offering a generous visible square reveal of Stainless Steel enhancing the installation.

These profiles offer superb resistance to principal chemical and atmospheric agents and are particularly recommended to protect steps in zones such as food processing industries, breweries, dairies, hospitals and external applications. Its smooth and non-porous surface makes it especially difficult for the adhesion and survival of bacteria and/or other microorganisms.

Genesis Stainless Steel profiles are supplied polished with a clear transparent film for added protection, before, during and after application - as standard (not 102).

Dimensions

Available in 2.5m lengths in depths of 8, 10 and 12mm.

Maintenance

Advanced Cleaning for Stainless Steel Discoloration.

Tarnish or Water Stains:

The first stage of corrosion is completely on the surface and is easily removed by most commercial metal polishes. Discoloration will be greater at indoor facilities due to the chlorine vapor trapped in an inside environment.

Lightning Rusting:

Rust is visible at this stage but little or no pitting has yet occurred. A stronger cleaning agent, such as Simi chrome Polish, is required.

Heavy Rusting:

A deep coat of rust with surface pitting can develop if corrosion has been left unchecked for a long time. For advanced corrosion naval jelly is recommended.

Surface Restoration: To remove or reduce pitting damage caused by corrosion has been left unchecked for a long time. Scotchbrite works well for this purpose. Work only in the direction of the existing grain and never use steel wool.

Installation

1. Select EQQ according to tile thickness.
2. Trowel tile adhesive over the area that forms the perimeter of the tiled covering.

3. Press the perforated anchoring leg of the EQQ, into the tile adhesive and align, mechanical fix if required
4. Trowel additional adhesive over the perforated anchoring leg to ensure full coverage.
5. Solidly embed the tiles so that the tiled surface is flush with the top of the profile (the profile should not be higher than the tiled surface, but rather up to approx. 1 mm lower).
6. Fill the joint completely with grout.


Allied Products:

EQQ has specially designed corner pieces, EDQ. They provide perfect corners with no sharp edges where mitring of the profile is required. Available in 8mm, 10mm and 12mm depths.



EQQ

Product Datasheet 9.18



General Cleaning and Maintenance

General Cleaning and Maintenance Suggestion for Stainless Steel

DO NOT:

Do not use steel wool or sandpaper, or mineral acids, bleaches or chlorine cleansers.

Do not add chlorine to your pool right next to your stainless steel, add it as far away as possible.

Do not store stainless steel in a closed area underneath steel beams to avoid corrosive condensation from dripping onto to the equipment and leaving brown spots.

Do not store stainless steel where it will attract and retain moisture or airborne contaminants and do not store equipment in the same areas as chlorine.

DO:

Rinse off stainless steel when exposed to Chlorine frequently with fresh water to wash away accumulated chemicals such as chlorine and wipe dry with a clean cloth. Especially try to clean immediately after use around chlorides (chlorine powder, seawater, etc.)

Clean frequently with a cleaner and water. Any cleaner that is safe for glass is usually safe for stainless steel.

Inspect frequently, if you notice discoloration, tarnish or water stains, increase the frequency of your freshwater rinses to reduce accumulated chemicals.

Remove any rust spots as soon as possible to prevent irreversible pitting.

Occasionally clean with borax, soda ash, or a non-abrasive commercial cleanser and water.

Stubborn Stains may be removed with a magnesium oxide, ammonia and water paste.

Consider the following periodic cleaning program:

- 1 can of powered cleanser
- 1 Scotchbrite pad
- 1 spray bottle
- cleaner 1 paste
- automotive wax

Directions:

Wet cleaning pad with fresh water (do not use pool water) and apply powered cleanser. Using gentle pressure, rub stained

Technical Details

and bromine used for sanitization are highly caustic chemicals for stainless steel and heat and humidity enhance the corrosiveness is not rustproof, particularly in the harsh environment of a swimming pool. Chlorine

areas in the same direction of the existing polishing grain until stains are removed. Rinse with clean water. Use cleaner degreaser to remove any stains. Thoroughly dry the stainless then apply wax. Let wax dry to a haze and buff to a shine with a clean dry cloth. Automotive waxes will provide added beauty and protection for your equipment.

of these chemicals. Regular cleaning is the best way to prevent corrosion and add to the service life for your profiles and any other stainless-steel equipment. The goal of your cleaning and maintenance program should be to keep the stainless steels protective Chromium oxide layer intact. This is what prevents corrosion. Varying Stages of contamination.

Stainless Steel AISI 304 / DIN1.4301 Surface BA1

C%	
Mn%	2.0
Si%	0.1
P%	0.75
S%	0.045
Cr%	0.03
Ni%	18-20
N%	10.5
	0.2-0.6

Stainless Steel AISI 430 / DIN 1.4016 Surface BA1

C%	0.0-0.08
Mn %	0.0-1.00
Si %	0.0-1.00
P %	0.0-0.04
S%	0.0-0.02
Cr %	16-18.00
Fe%	Balance

+44 (0)1642 713000 info@genesis-gs.com
www.genesis-gs.com

 **Genesis**
For the Perfect Finish